

Appln. No. 10/816,423

Attorney Docket No. 10541-1930

I. Amendments to the Claims

1. (Cancelled)

2. (Currently Amended) The system according to claim [[1]] 4, wherein the first signal generator is a pulse width modulator.

3. (Currently Amended) The system according to claim [[1]] 4, wherein the analog to digital converter is connected to a first coil output and a second coil output of the fluxgate.

4. (Currently Amended) ~~The system according to claim 1, A~~
fluxgate magnetometer comprising:

a fluxgate;

a digital processor in communication with the fluxgate, the digital processor including an analog to digital converter configured to digitize a back EMF signal from the fluxgate generating digitized back EMF signal, and a first signal generator configured to generate a fluxgate driving signal, wherein the digital processor is configured to reverse the sign of the digitized back EMF signal at a frequency corresponding to two times the frequency of the fluxgate drive signal.

BRINKS
HOFER
GILSON
ALIONE

BRINKS HOFER GILSON & LIONE
PO Box 10395
Chicago, IL 60610

Appl. No. 10/816,423

Attorney Docket No. 10541-1930

5. (Original) The system according to claim 4, wherein the digital processor is configured to integrate the digitized back EMF signal thereby generating a summation signal.

6. (Original) The system according to claim 5, wherein the digital processor is configured to integrate the digitized back EMF signal using a Reimann Sum calculation.

7. (Original) The system according to claim 5, wherein the digital processor is configured to modulate the fluxgate driving signal generated by the signal generator based on the summation signal.

8. (Original) The system according to claim 5, wherein the digital processor includes a digital to analog converter configured to convert the summation signal into an analog output signal.

9. (Original) The system according to claim 8, wherein the digital to analog converter is in electrical communication with a signal amplifier configured to generate an amplified analog output signal.

10. (Cancelled)

11. (Cancelled)



BRINKS HOFER GILSON & LIONE
PO Box 10395
Chicago, IL 60610

Appln. No. 10/816,423

Attorney Docket No. 10541-1930

12. (Currently Amended) ~~The system according to claim 11,~~
further comprising A fluxgate magnetometer comprising:

a fluxgate;

a digital processor in communication with the fluxgate, the digital processor including an analog to digital converter configured to digitize a back EMF signal from the fluxgate generating digitized back EMF signal, and a first signal generator configured to generate a fluxgate driving signal;

a current sourcing circuit configured to receive the fluxgate driving signal from the first signal generator of the digital processor, and transmit a current amplified driver signal to the fluxgate;

a resistor connected in electrical series between the first signal generator and the current sourcing circuit, and a capacitor is in electrically parallel connection between the resistor and an electrical ground; and

a second signal generator in electrical communication with the current sourcing circuit, wherein the current sourcing circuit includes a first, second, third, and fourth transistor, the first, second, third, and fourth transistor in electrical communication with the fluxgate.

13. (Original) The system according to claim 12, wherein the first, second, third, and fourth transistors are MOSFET transistors.



BRINKS HOFER GILSON & LIONE
PO Box 10395
Chicago, IL 60610

Appln. No. 10/816,423

Attorney Docket No. 10541-1930

14. (Original) The system according to claim 13 wherein the second and third transistor is in electrical communication with the first signal generator, and the first and fourth transistors are in electrical communication with the second signal generator.

15. (Original) The system according to claim 14, wherein the second and third transistors are N-channel MOSFETs, and wherein the first and fourth transistors are P-channel MOSFETs.

16. (Cancelled)

17. (Currently Amended) The system according to claim ~~[[16]]~~ 19, wherein the first signal generator is a pulse width modulator.

18. (Currently Amended) The system according to claim ~~[[16]]~~ 19, wherein the analog to digital converter is connected to a first coil output and a second coil output of the fluxgate.

19. (Currently Amended) ~~The system according to claim 16, A~~
sensor for measuring torque comprising:

a fluxgate including a magnetic shaft mounted such that a torque may be applied causing a rotation of the shaft, such that a rotation of the shaft creates a back EMF in a coil;

BRINKS
HOFER
GILSON
LIONE

BRINKS HOFER GILSON & LIONE
PO Box 10395
Chicago, IL 60610

Appln. No. 10/816,423

Attorney Docket No. 10541-1930

a digital processor in communication with the fluxgate, the digital processor including an analog to digital converter configured to digitize the back EMF signal from the fluxgate generating a digitized back EMF signal, and a first signal generator configured to generate a fluxgate driving signal, wherein the digital processor is configured to reverse the sign of the digitized back EMF signal at a frequency corresponding to two times the frequency of the fluxgate drive signal.

20. (Original) The system according to claim 19, wherein the digital processor is configured to integrate the digitized back EMF signal thereby generating a summation signal.

21. (Original) The system according to claim 20, wherein the digital processor is configured to integrate the digitized back EMF signal using a Reimann Sum calculation.

22. (Original) The system according to claim 20, wherein the digital processor is configured to modulate the fluxgate driving signal generated by the signal generator based on the summation signal.

23. (Original) The system according to claim 20, wherein the digital processor includes a digital to analog converter configured to convert the summation signal into an analog output signal.



BRINKS HOFER GILSON & LIONE
PO Box 10395
Chicago, IL 60610

Appln. No. 10/816,423

Attorney Docket No. 10541-1930

24. (Original) The system according to claim 23, wherein the digital to analog converter is in electrical communication with a signal amplifier configured to generate an amplified analog output signal.

25. (Cancelled)

26. (Cancelled)

27. (Currently Amended) ~~The system according to claim 26, A~~
sensor for measuring torque comprising:

a fluxgate including a magnetic shaft mounted such that a torque may be applied causing a rotation of the shaft, such that a rotation of the shaft creates a back EMF in a coil;

a digital processor in communication with the fluxgate, the digital processor including an analog to digital converter configured to digitize the back EMF signal from the fluxgate generating a digitized back EMF signal, and a first signal generator configured to generate a fluxgate driving signal;

a current sourcing circuit configured to receive the fluxgate driving signal from the first signal generator of the digital processor, and transmit a current amplified driver signal to the fluxgate;



BRINKS HOFER GILSON & LIONE
PO Box 10395
Chicago, IL 60610

Appln. No. 10/816,423

Attorney Docket No. 10541-1930

a resistor is connected in electrical series between the first signal generator and the current sourcing circuit, and a capacitor is in electrically parallel connection between the resistor and an electrical ground; and

further comprising a second signal generator in electrical communication with the current sourcing circuit, wherein the current sourcing circuit includes a first, second, third, and fourth transistor, the first, second, third, and fourth transistor in electrical communication with the fluxgate.

28. (Original) The system according to claim 27, wherein the first, second, third, and fourth transistors are MOSFET transistors.

29. (Original) The system according to claim 28, wherein the second and third transistor is in electrical communication with the first signal generator, and the first and fourth transistors are in electrical communication with the second signal generator.

30. (Original) The system according to claim 29, wherein the second and third transistors are N-channel MOSFETs, and wherein the first and fourth transistors are P-channel MOSFETs.



BRINKS HOFER GILSON & LIONE
PO Box 10395
Chicago, IL 60610